CASE™
CANADA SECURITY

CS-CI4 Window-wifi

4MP PhotonX Wi-Fi Window Camera

Value Series



6 Years WARRANTY

24/7 Support

NDAA COMPLIANT

KEY FEATURES

- Plastic housing
- Up to 4MP, 2560x1440@15fps
- S+265/H265
- Color:0.0005Lux @ (F1.0，AGC ON), B/W:0.0002Lux @(F1.0，AGC ON)；0Lux with IR
- IR range up to 30m
- 1×Built-in Mic, 1×Built-in Loudspeaker
- Support microSD/microSDHC/microSDXC card,up to 256GB
- Operating conditions -10℃-45℃(14°F~113°F)), ≤95%RH
- DC5V,USB type-C,Max.10W

Email: sales@canadasecurity.com
Website: canadasecurity.com
US : +1 301 900 1000
CA : +1 289 800 9000

CASE™
CANADA SECURITY


SPECIFICATIONS

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.0005Lux @ (F1.0，AGC ON),B/W:0.0002Lux @(F1.0，AGC ON)；0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	WDR
S/N	⩾52dB
Angle Adjustment	-10~10°(T)
Lens	
Lens Type	Fixed focal lens
Focal Length	4mm
Lens Mount	M12
Aperture Range	F1.0
Aperture Type	Fixed
Field of View	86.4°(H); 48.6°(V); 98°(D)
Pan&Tilt	
Pan Speed	45°/s
Tilt Speed	30°/s
Preset	64
Illuminator	
IR LEDs	2
IR Distance	Up to 30m
Wavelength	850nm
Compression Standard	
Video Compression	S+265/H265
Video Bit Rate	32k~2Mbps
Audio Compression	AAC/G.711A
Audio Sampling Rate	8K/16kHz
Image	
Max. Resolution	4MP,2560x1440@15fps
Main Stream	PAL:15fps(2560×1440,1280×720)
Sub Stream	PAL:15fps(1280×720)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes

White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters or 16 Chinese characters per region; Adaptive character size; Lattice
Defog	Yes
Feature	
Exceptions Alarm	Disk Full; Disk R/W Error
Linkage Method	Trigger Sound; Trigger Recording; Trigger Capture
Video Analytics	Smart Alarm(Human、Vehicle)
Network	
Protocols	TCP/IP; ICMP; DNS; NTP; IPv4; SSH; Unicast; Multicast
Remote Connection	⩽2
Client	CASE Station; work with hey google; work with alexa
Mobile Client	CASE Connect
work with hey google	Yes
works with alexa	Yes
Wi-Fi	
Transmission Distance	Up tp 30m(based on actual environment)
Wireless Standard	IEEE802.11a/IEEE802.11b/ 802.11g/802.11n
Frequency Range	2.4G：2.4 GHz ~ 2.4835 GHz 5G：5.17 GHz~5.25 GHz，5.735 GHz~5.835 GHz
Channel Bandwidth	20/40MHz
Wi-Fi Security	WPA-PSK/WPA2-PSK
Interface	
Built-in Mic	1×Built-in Mic
Built-in Speaker	1×Built-in Loudspeaker
Reset Button	Yes
On-board Storage	Support microSD/microSDHC/microSDXC card,up to 256GB
Bluetooth Provisioning	Yes
General	
Operating Temperature	-10°C-45°C(14°F~113°F))
Operating Humidity	⩽95%RH
Storage Temperature	-5°C-50°C(14°F~113°F))
Storage Humidity	0~95%RH(non-condensing)
Power Supply	DC5V,USB type-C,Max.10W
Protection	ESD6000V
Boundary Dimensions	65(L)43(W)65(H)mm
Package Dimensions	92(L)92(W)107(H)mm
GrossWeight	0.371kg

NetWeight	0.171kg

DIMENSIONS (Unit: mm)



Softwares

Case Connect android

Case Connect iPhone

Case Station

Email: sales@canadasecurity.com
Website: canadasecurity.com
US : +1 301 900 1000
CA : +1 289 800 9000