CASE™
CANADA SECURITY

CS-CP12 Solar-wifi

12MP(3 X 4MP) NightBright Solar Wi-Fi PT Camera



Sharp Series

3 Years WARRANTY

24/7 Support

NDAA COMPLIANT

KEY FEATURES

- Plastic housing
- Up to 4MP,2560×1440@12fps
- S+265/H265
- Color:0.02Lux@(F1.6,AGC ON),B/W:0.01Lux@(F1.6，AGC ON)； 0Lux with IR
- IR range up to 50m
- 1×Built-in Mic, 1×Built-in Loudspeaker
- Support microSD/microSDHC/microSDXC card,up to 256GB
- Operating conditions -30°C~60°C(-22°F~140°F), ⩽95%RH
- DC5V±25%,Max. 10W
- IP65

Email: sales@canadasecurity.com
Website: canadasecurity.com
US : +1 301 900 1000
CA : +1 289 800 9000

CASE™
CANADA SECURITY


SPECIFICATIONS

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0.01Lux@(F1.6，AGC ON)；0Lux with IR
Shutter Time	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Yes
WDR	DWDR
S/N	⩾52dB
Angle Adjustment	0~345°(P); -10~90°(T)
Lens	
Lens Type	Fixed focal lens
Focal Length	Panorama:2.8mm,Detail:4mm+6mm,12x electronic hybrid zoom supported
Lens Mount	M12
Aperture Range	F1.6
Aperture Type	Fixed
Field of View	2.8mm：92.3°(H)；4mm：78.0°(H); 2.8mm：52.0°(V)；4mm：41.7°(V); 2.8mm：104.3°(D)；4mm：90.0°(D)
Pan&Tilt	
Pan Speed	30°/s
Tilt Speed	25°/s
Preset	64
Illuminator	
IR LEDs	8
IR Distance	Up to 50m
Wavelength	850nm
White LEDs	8
Whitelight Distance	30m
Red and Blue Alarm Flash	Yes
Compression Standard	
Video Compression	S+265/H265
Video Bit Rate	32k~2Mbps
Audio Compression	AAC/G.711A
Audio Sampling Rate	8kHz/16kHz
Image	
Max. Resolution	4MP,2560×1440@12fps
Main Stream	PAL:12fps(2560×1440,1280×720)
Sub Stream	PAL:12fps(1280×720)
BLC	Yes

HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-Auto/Manual/Sunshine/Nature Light/Warmlight Lamp/Daylight Lamp/Filament Lamp/Lock White Balance
OSD	Overlay of additional characters in 1 regions, 1 line, with a maximum of 48 characters per region; Adaptive character size; Lattice
Defog	Yes
Feature	
Exceptions Alarm	Disk Full; Disk R/W Error
Linkage Method	Trigger Sound; Trigger Recording; Trigger Capture
Video Analytics	Smart Alarm（human and vehicle detection）
Auto-Tracking	Auto-Tracking
Network	
Protocols	TCP/IP; ICMP; DNS; NTP; IPv4; SSH; Unicast; Multicast
Remote Connection	≤2
Client	CASE Station; works with hey Google; works with Alexa
Mobile Client	CASE Connect
Wi-Fi	
Transmission Distance	Up tp 50m(based on actual environment)
Wireless Standard	IEEE802.11a/IEEE802.11b/ 802.11g/802.11n
Frequency Range	2.4G：2.4 GHz ~ 2.4835 GHz 5G：5.17 GHz~5.25 GHz，5.735 GHz~5.835 GHz
Channel Bandwidth	20/40MHz
Wi-Fi Security	WPA-PSK/WPA2-PSK
Interface	
Built-in Mic	1×Built-in Mic
Built-in Speaker	1×Built-in Loudspeaker
Reset Button	Yes
On-board Storage	Support microSD/microSDHC/microSDXC card,up to 256GB
Bluetooth Provisioning	Yes
Super Resolution Zoom	Super Resolution Zoom
General	
Operating Temperature	-30°C~60°C(-22°F~140°F)
Operating Humidity	≤95%RH
Storage Temperature	-20°C~50°C(-4°F~122°F)
Storage Humidity	10%~95%RH(non-condensing)
Power Supply	DC5V±25%,Max. 10W
Protection	ESD6000V; IP65

Boundary Dimensions	115(L)145(W)234(H)mm
Package Dimensions	363(L)253(W)200(H)mm
GrossWeight	2.21kg
NetWeight	0.96kg

DIMENSIONS (Unit: mm)



Softwares

Case Connect android

Case Connect iPhone

Case Station

Email: sales@canadasecurity.com
Website: canadasecurity.com
US : +1 301 900 1000
CA : +1 289 800 9000