

CS-VIK 27

IP Video Intercom Kit



KEY FEATURES

- Plug & Play
- User friendly interface
- Standard PoE
- One -touch calling
- Remote unlocking
- CCTV integration



Email: sales@canadasecurity.com
Website: canadasecurity.com

US : +1 301 900 1000
CA : +1 289 800 9000

SPECIFICATIONS

Model: Single button villa panel

Solution	
CPU, RAM, ROM	V3LP ROM 128MB RAM 64MB
CMF	
Colour	Black
Material	Aluminum panel+Tempered glass+Plastic nameplate button+Plastic cover
Finishing	Die-casting and painting
Audio	
Microphone	Yes
Speaker	Yes
Narrowband audio codec	G.711
Full duplex	Yes
Video	
Pixels	2MP
Angle	Horizontal:110°, Vertical:67°, Diagonal:127°
Video codec	H.264
Video resolution	Up to 1080P
FPS	25
WDR	No
Night vision	White Leds
Access	
RFID card reader	13.56MHz(NFC)and 125kHz
BLE	No
Wiegand	Yes
Network	
WIFI	No
Ethernet	Single ethernet port
Hardware Interface	
Relay	2
Power unlock	No
RS485	Yes
Tamper alarm	Yes
Alarm input	2

Alarm output	2
Door sensor	Yes
Exit buton	Yes
Reset	Yes
Micro SD card	No
Power	
PoE	Yes
DC power supply	12V/1A
Power consumption	<10 W
Others	
IP/IK level	IP65 IK08
Indicator light	Yes
Nameplate	Yes
IR sensor	No
Motion detection	No
Photoresistor	Yes
Installation	
Installation	Surface mount
Working Temperature	
Working Temperature	-40°C~+55°C

Model: 7 inch Linux indoor monitor

Solution	
RAM	128MB
ROM	128MB
System	Linux
Design	
Colour	Black+Darkgray
Material	Plastic
Screen	
Type	TFT
Resolution	1024×600
Audio	
Speaker	Yes
Mic	Yes
Narrowband audio codec	G.711

Video

Camera	No
--------	----

Network

WIFI	Yes
------	-----

Ethernet	Single ethernet port
----------	----------------------

Hardware Interface

Relay	1
-------	---

RS485	Yes
-------	-----

Tamper alarm	No
--------------	----

Alarm zones	8
-------------	---

12V output	No
------------	----

Doorbell in	Yes
-------------	-----

Reset	No
-------	----

Micro USB	For debug only
-----------	----------------

Micro SD card	Yes
---------------	-----

Power

PoE	Yes
-----	-----

DC power supply	12V
-----------------	-----

Power consumption	less than 6W
-------------------	--------------

Others

Languages	English, Spanish, German, Polish, Russian, Turkish, Hebrew, Arabic, Portuguese, French, Italian, Slovak, Vietnamese, and Dutch
-----------	--

Installation

Installation	Surface mount
--------------	---------------

Working Temperature

Working Temperature	-10°C~+55°C
---------------------	-------------

DIMENSIONS:

